



## PT-D600 Professional PC Connectable Electronic Labeller

PC Connectable Desktop Electronic Labeller with Colour LCD screen and Label design software.

- Large colour Graphic display with backlight
- Auto tapes and colour detection
- Print on 3.5, 6, 9, 12, 18 and 24mm TZe laminated labels
- Built-in editable label design templates
- Automatic label cutter

LABELS THAT STICK. P.touch

## PT-D600

PT-D600 electronic labeller can create durable fade resistant labels by using easy to use integrated labelling functions and print directly from PC or Mac OS® systems connection. Fully equipped with the versatile P-touch Editor labelling design software, large colour LCD graphic display with label preview function and easy-to-use wide PC style keyboard, labels can be created easily in a variety of sizes and colours.









Automatic label cutter

Print labels from PC or Mac  $\mathrm{OS}^{\mathbb{R}}$  systems

High resolution colour display

14 fonts, 99 frames and over 600 symbols

## **Technical Specification**

General	
Hardware type	Desktop
Keyboard	Qwerty & Numeric
Display type	LCD (Backlight)
LCD Display	20-character x 3 lines LCD Display
Built-in Languages	20 languages (English, German, French, Spanish, Portuguese, Portuguese-Bra, Italian, Dutch, Norwegian, Swedish, Finnish, Hungarian, Czech, Polish, Romanian, Slovene, Slovak, Croatian, Turkish)
Feed	Yes
Cable labelling function	3 kinds (Cable Wrap, Cable Flag, FacePlate)
Label Collection	25 kinds
Labeller	
Print Engine	Thermal
Print speed	30mm per second
Resolution	180dpi / 180 x 360dpi in high resolution
Emulation	Raster mode
Max Print Height	18mm
Max Print Length	300mm
Tape cutter	Auto
Tape length setting	Auto / 30mm - 300mm
Tape length	8m
Tape Colour Detection	Yes
Fonts	14 (Helsinki, Brussels, Belgium, Florida, Los Angeles, San Diego, US, Calgary, Atlanta, Adams, Brunei, Sofia, Germany, Letter Gothic) or PC Select
Font sizes	7 kinds (Auto, 6, 9, 12, 18, 24, 36, 42pt) or PC Select
Font styles	11 (Normal, Bold, Outline, Shadow, Solid, Italic, Italic Bold, Italic Outline, Italic Shadow, Italic Solid, Vertical, Vertical Bold) or PC Select
Font width	5 (x2, x3/2, Normal, x 2/3, x1/2)
Frames and Backgrounds	99 Frames
Characters and Symbols	825 Characters / 617 Symbols

Time and Date Feature	Yes
Memory	Text Buffer: 280 Characters /
Barcodes	Label Buffer: 2,800 Characters 9 (CODE39, CODE128, ITF 2/5, EAN13, EAN8, UPC-A, UPC-E, CODABAR, GS1-128 (UCC/EAN128))
Auto number / format Underline Multi-line Print Repeat Print Mirror Print Vertical Print Print Preview Software	Yes Yes, (1 - 99) Yes Yes, (in the style setting) Yes, (Label / Print Preview)
	Mindows® OC Customes and Mac OC®
Software supplied	Windows <sup>®</sup> OS Systems and Mac OS <sup>®</sup> Systems Printer Drivers, P-touch Editor version 5.0 software
Connectivity	
Interface Operating System	USB Windows <sup>®</sup> 7 / 8 (32, 64bit), Vista <sup>®</sup> (32, 64bit) Mac OS <sup>®</sup> Systems X 10.6 or greater
Consumable	
Tape type Tape width	TZe laminated and non-laminated tapes 3.5, 6, 9, 12, 18, 24mm
Weight and Measurement	
Size Weight Size with carton Weight with carton	201mm (W) x 86mm (H) x 192mm (D) 940g (without tape & batteries) 260mm (W) x 319mm (H) x 121mm (D) 1.75 kg
Option Optional Power (not included)	6pcs of AA Alkaline batteries
Power Supply	opes of the transfer batteries
Batteries (not included) AC Power adapter Auto Power off	6 pcs of AA batteries (LR06 / Ni-MH HR06) AD-E001A AC Power adapter (included) 5 minutes - Battery, 60 minutes - USB 8 hours - AC Power adapter
Others	
Package content	PT-D600 Electronic Labeller USB 2.0 cable (Mini-B type connector) AD-E001A AC Power adapter TZe-251 24mm Black on White tape (4m long) User guide





